- 1 -

DRILLING SYSTEM AND METHOD

The present invention relates to a drilling system
and method for drilling a bore hole into an earth
formation.

The exploration and production of hydrocarbons from
subsurface formations ultimately requires a method to
reach for and extract the hydrocarbons from the
formation. This is typically achieved by drilling a well
with a drilling rig. In its simplest form, this
constitutes a land-based drilling rig that is used to
support and rotate a drill string, comprised of a series
of drill tubulars with a drill bit mounted at the end.
Furthermore, a pumping system is used to circulate a
fluid, comprised of a base fluid, typically water or oil,
and various additives down the drill string, the fluid
then exits through the rotating drill bit and flows back
to surface via the annular space formed between the
borehole wall and the drill string. The drilling fluid
serves the following purposes: (a) provide support to the
borehole wall, (b) prevent or, in case of under balanced
drilling (UBD), control formation fluids or gasses from
entering the well, (c) transport the cuttings produced by
the drill bit to surface, (d) provide hydraulic power to
tools fixed in the drill string and (e) cooling of the
bit. After being circulated through the well, the
drilling fluid flows back into a mud handling system,
generally comprised of a shaker table, to remove solids,
a mud pit and a manual or automatic means for addition of
various chemicals or additives to keep the properties of
the returned fluid as required for the drilling
operation. Once the fluid has been treated, it is

circulated back into the well via re-injection into the
top of the drill string with the pumping system.

During drilling operations, the drilling fluid exerts
a pressure against the well bore inside wall that is
mainly built-up of a hydrostatic part, related to the
weight of the mud column, and a dynamic part related
frictional pressure losses caused by, for instance, the
fluid circulation rate or movement of the drill string.

The fluid pressure in the well is selected such that,
while the fluid is static or circulated during drilling
operations, it does not exceed the formation fracture
pressure or formation strength. If the formation strength
is exceeded, formation fractures will occur which will
create drilling problems such as fluid losses and
borehole instability. On the other hand, in overbalanced
drilling the fluid density is chosen such that the
pressure in the well is always maintained above the pore
pressure to avoid formation fluids entering the well,
while during UBD the pressure in the well is maintained
just below the power pressure to controllably allow
formation fluids entering the well (primary well
control).

The pressure margin with on one side the pore
pressure and on the other side the formation strength is
known as the "Operational Window".

For reasons of safety and pressure control, a Blow-
Out Preventer (BOP) can be mounted on the well head,
below the rig floor, which BOP can shut off the wellbore
in case formation fluids or gas should enter the wellbore
(secondary well control) in an unwanted or uncontrolled
way. Such unwanted inflows are commonly referred to as
"kicks". The BOP will normally only be used in emergency
i.e. well-control situations.

In US patent 6,035,952, to Bradfield et al. and
assigned to Baker Hughes Incorporated, a closed well bore

- 3 -

system is used for the purposes of underbalanced
drilling, i.e., the annular pressure is maintained below
the formation pore pressure.

In US patent 6,352,129 (Shell Oil Company) a method
and system are described to control the fluid pressure in
a well bore during drilling, using a back pressure pump
in fluid communication with an annulus discharge conduit,
in addition to a primary pump for circulating drilling
fluid through the annulus via the drill string.

An accurate control of the fluid pressure in the well
bore is facilitated by an accurate knowledge of the down
hole pressure. However, in a borehole with a variably
rotating drill string, and with possibly all kinds of
down hole subs that are driven by the drilling fluid
circulation flow, it is a problem to monitor the down
hole pressure in real time. Measurements of the pressure
of the drilling fluid in the drill string, or in the bore
hole, close to the surface level are often too far
removed from the lower end of the bore hole to provide an
accurate basis for calculating or estimating the actual
down hole pressure. On the other hand, the currently
available data transfer rates are too low for using
direct down hole pressure data taken by a measurement
while drilling sensor as a real-time feed back control
signal.

It is thus an object of the invention to provide a
system and a method for drilling a bore hole into an
earth formation that allows for improved control of the
fluid pressure in the well bore.

According to the invention, there is provided a
drilling system for drilling a bore hole into an earth
formation, the bore hole having an inside wall, and the
system comprising:

- 4 -

- a drill string reaching into the bore hole leaving a drilling fluid return passage between the drill string and the bore hole inside wall;
- a drilling fluid discharge conduit in fluid communication with the drilling fluid return passage;
- pump means for pumping a drilling fluid through the drill string into the bore hole and to the drilling fluid discharge conduit via the drilling fluid return passage;
- back pressure means for controlling the drilling fluid back pressure;
- fluid injection means comprising an injection fluid supply passage fluidly connecting an injection fluid supply to the drilling fluid return passage and further comprising an injection fluid pressure sensor arranged to provide a pressure signal in accordance with an injection fluid pressure in the injection fluid supply passage;
- back pressure control means for controlling the back pressure means whereby the back pressure control means is arranged to receive the pressure signal and to regulate the back pressure means in dependence of at least the pressure signal.

The invention also provides a drilling method for drilling a bore hole into an earth formation, the bore hole having an inside wall, the drilling method comprising the steps of:
- deploying a drill string into the bore hole and forming a drilling fluid return passage between the drill string and the bore hole inside wall;
- pumping a drilling fluid through the drill string into the bore hole and via the drilling fluid return passage to a drilling fluid discharge conduit arranged in fluid communication with the drilling fluid return passage;
- controlling a drilling fluid back pressure by controlling back pressure means;

- 5 -

- injecting an injection fluid from an injection fluid
supply via an injection fluid supply passage into the
drilling fluid in the drilling fluid return passage;
- generating a pressure signal in accordance with an
5   injection fluid pressure in the injection fluid supply
passage;
- controlling the back pressure means, which
controlling comprises regulating the back pressure means
in dependence of at least the pressure signal.

10   The injection fluid pressure in the injection fluid
supply passage represents a relatively accurate indicator
for the drilling fluid pressure in the drilling fluid gap
at the depth where the injection fluid is injected into
the drilling fluid gap. Therefore, a pressure signal

15   generated by an injection fluid pressure sensor anywhere
in the injection fluid supply passage can be suitably
utilized, for instance as an input signal for controlling
the back pressure means, for monitoring the drilling
fluid pressure in the drilling fluid return passage.

20   The pressure signal can, if so desired, optionally be
compensated for the weight of the injection fluid column
and/or for the dynamic pressure loss that may be
generated in the injection fluid between the injection
fluid pressure sensor in the injection fluid supply

25   passage and where the injection into the drilling fluid
return passage takes place, for instance, in order to
obtain an exact value of the injection pressure in the
drilling fluid return passage at the depth where the
injection fluid is injected into the drilling fluid gap.

30   Unlike the drilling fluid passage inside the drill
string, the injection fluid supply passage can preferably
be dedicated to one task, which is supplying the
injection fluid for injection into the drilling fluid
gap. This way, its hydrostatic and hydrodynamic

35   interaction with the injection fluid can be accurately

- 6 -

determined and kept constant during an operation, so that
the weight of the injection fluid and dynamic pressure
loss in the supply passage can be accurately established.

The invention is at least applicable to pressure
5   control during under-balanced drilling operations, at-
balance drilling operations, over-balance drilling
operations or completion operations.

It will be understood that the invention is enabled
with only one injection fluid pressure sensor, but that a
10   plurality of injection fluid pressure sensors can be
utilized, if so desired, for instance positioned in
mutually different locations.

It is remarked that WO 02/084067 describes a drilling
well configuration wherein the drilling fluid gap is
15   formed by an inner well bore annulus, and an injection
fluid supply passage is provided in the form of a second,
outer annulus, for bringing the injection fluid from the
surface level to a desired injection depth. Fluid is
injected into the inner annulus for dynamically
20   controlling bottom hole circulation pressure in the well
bore wherein a high injection rate of a light fluid
results in a low bottom hole pressure.

In contrast, the present patent application utilizes
back pressure means for controlling the bottom hole
25   pressure, whereby the injection fluid injection pressure
is utilized for controlling the back pressure means. It
has been found that, by controlling back pressure means
in response of the injection fluid injection pressure,
the down hole pressure is more accurately controllable
30   and more stable than by controlling the down hole
pressure by directly regulating the injection fluid
injection rate.

Nevertheless, the injection fluid injection rate may
be controlled in concert with controlling the back
35   pressure means. This is of particular advantage when

- 7 -

starting or stopping circulation in order to avoid the injection fluid injection rate being maintained at unrealistic values.

In a preferred embodiment, the pressure difference of the drilling fluid in the drilling fluid return passage in a lower part of the bore hole stretching between the injection fluid injection point and the bottom of the well bore, can be calculated using a hydraulic model taking into account inter alia the well geometry. Since the hydraulic model is herewith only used for calculating the pressure differential over a relatively small section of the bore hole, the precision is expected to be much better than when the pressure differential over the entire well length must be calculated.

In order to facilitate the accuracy of bottom hole pressure determination, the injection fluid is preferably injected as close as possible to the bottom of the bore hole.

The injection fluid supply passage is preferably led to or close to the surface level from where the drill string reaches into the bore hole, thereby providing an opportunity to generate the pressure signal at surface or close to the surface. This is more convenient, and in particular allows for faster monitoring of the pressure signal, than when the pressure signal would be generated at great depth below the surface level.

The injection fluid can be a liquid or a gas. Preferably, the injection fluid injection system is arranged to inject an injection fluid having a mass density lower than that of the drilling fluid. By injecting a lower density injection fluid, the hydrostatic component to the down hole pressure is reduced. This allows for a higher dynamic range of control for the back pressure means.

- 8 -

However, the injection fluid is preferably provided
in the form of a gas, particularly an inert gas such as
for example nitrogen gas (N2). The dynamic pressure loss
of the gas in the injection fluid supply passage can
5   optionally be taken into account, but its contribution to
the pressure signal is expected to be low compared to the
weight of the gas column. Thus, the gas pressure
compensated for the weight of the gas column may for
practical purposes be assumed to be almost equal to the
10   drilling fluid pressure in the drilling fluid gap at the
injection depth.

The invention will now be illustrated by way of
example, with reference to the accompanying drawing
wherein

15   Fig. 1 is a schematic view of a drilling apparatus
according to an embodiment of the invention;

Fig. 2 schematically shows a schematic well
configuration in a drilling system in accordance with the
invention;

20   Fig. 3 is a block diagram of the pressure monitoring
and control system utilized in an embodiment of the
invention;

Fig. 4 is a functional diagram of the operation of
the pressure monitoring and control system;

25   Fig. 5 is a schematic view of a drilling apparatus
according to another embodiment of the invention;

Fig. 6 is a schematic view of a drilling apparatus
according to yet another embodiment of the invention.

In these figures, like parts carry identical
30   reference numerals.

Fig. 1 is a schematic view depicting a surface
drilling system 100 employing the current invention. It
will be appreciated that an offshore drilling system may
likewise employ the current invention.

- 9 -

The drilling system 100 is shown as being comprised
of a drilling rig 102 that is used to support drilling
operations. Many of the components used on a rig 102,
such as the kelly, power tongs, slips, draw works and
other equipment are not shown for ease of depiction. The
rig 102 is used to support drilling and exploration
operations in a formation 104. A borehole 106 has already
been partially drilled.

A drill string 112 reaches into the bore bole 106,
thereby forming a well bore annulus between the bore hole
wall and the drill string 112, and/or between an optional
casing 101 and the drill string 112. One of the functions
of the drill string 112 is to convey a drilling
fluid 150, the use of which is required in a drilling
operation, to the bottom of the bore hole and into the
well bore annulus.

The drill string 112 supports a bottom hole assembly
(BHA) 113 that includes a drill bit 120, a mud motor 118,
a sensor package 119, a check valve (not shown) to
prevent backflow of drilling fluid from the well bore
annulus into the drill string.

The sensor package 119 may for instance be provided
in the form of a MWD/LWD sensor suite. In particular it
may include a pressure transducer 116 to determine the
annular pressure of drilling fluid in or near the bottom
of the hole.

The BHA 113 in the shown embodiment also includes a
telemetry package 122 that can be used to transmit
pressure information, MWD/LWD information as well as
drilling information to be received at the surface. A
data memory including a pressure data memory may be
provided for temporary storage of collected pressure data
before transmittal of the information.

The drilling fluid 150 may be stored in a
reservoir 136, which in Fig. 1 is depicted in the form of

- 10 -

a mud pit. The reservoir 136 is in fluid communications
with pump means, particularly primary pump means,
comprising one or more mud pumps 138 that, in operation,
pump the drilling fluid 150 through a conduit 140. An
5   optional flow meter 152 can be provided in series with
one or more mud pumps, either upstream or downstream
thereof. The conduit 140 is connected to the last joint
of the drill string 112.

During operation, the drilling fluid 150 is pumped
10   down through the drill string 112 and the BHA 113 and
exits the drill bit 120, where it circulates the cuttings
away from the bit 120 and returns them up a drilling
fluid return passage 115 which is typically formed by the
well bore annulus. The drilling fluid 150 returns to the
15   surface and goes through a side outlet, through drilling
fluid discharge conduit 124 and optionally through
various surge tanks and telemetry systems (not shown).

Referred is now also to Fig. 2, showing schematically
the following details of the well configuration that
20   relate to an injection fluid injection system for
injecting an injection fluid into the drilling fluid that
is contained in the drilling fluid return passage. An
injection fluid supply passage is provided in the form of
an outer annulus 141. The outer annulus 141 fluidly
25   connects an injection fluid supply 143 with the drilling
fluid return passage 115, in which gap an injection fluid
can be injected through injection point 144. Suitably,
the injection fluid supply 143 is located on the surface.

A variable flow-restricting device, such as an
30   injection choke or an injection valve, is optionally
provided to separate the injection fluid supply
passage 141 from the drilling fluid return passage 115.
Herewith it is achieved that injection of the injection
fluid into the drilling fluid can be interrupted while

- 11 -

maintaining pressurisation of the injection fluid supply
passage.

   Suitably, the injection fluid has a lower density
than the drilling fluid, such that the hydrostatic
5   pressure in the bottom hole area, in the vicinity of the
drill bit 120, is reduced due to a lower weight of the
body of fluid present in the fluid return passage 115.

   Suitably, the injection fluid is injected in the form
of a gas, which can be, for example, nitrogen gas. An
10   injection fluid pressure sensor 156 is provided, in fluid
communication with the injection fluid supply passage,
for monitoring a pressure of the injection fluid in the
injection fluid supply passage 144. The injection fluid
supply passage 141 is led to the surface level on the
15   rig, so that the injection fluid pressure sensor 156 can
be located at the surface level and the pressure data
generated by the injection fluid pressure sensor 156 is
readily available at surface.

   During circulation of the drilling fluid 150 through
20   the drill string 112 and bore hole 106, a mixture of
drilling fluid 150, possibly including cuttings, and the
injection fluid flows through an upper part 149 of the
annulus 115, down stream of the injection point 144.
Thereafter the mixture proceeds to what is generally
25   referred to as the backpressure system 131.

   A pressure isolating seal is provided to seal against
the drill string and contain a pressure in the well bore
annulus. In the embodiment of Fig. 1, the pressure
isolating seal is provided in the form of a rotating
30   control head on top of the BOP 142, through which
rotating control head the drill string passes. The
rotating control head on top of the BOP forms, when
activated, a seal around the drill string 112, isolating
the pressure, but still permitting drill string rotation
35   and reciprocation. Alternatively a rotating BOP may be

- 12 -

utilized. The pressure isolating seal can be regarded to
be a part of the back pressure system.

Referring to Fig. 1, as the mixture returns to the
surface it goes through a side outlet below the pressure
isolating seal to back pressure means arranged to provide
an adjustable back pressure on the drilling fluid mixture
contained in the well bore annulus 115. The back pressure
means comprises a variable flow restrictive device,
suitably in the form of a wear resistant choke 130. It
will be appreciated that there exist chokes designed to
operate in an environment where the drilling fluid 150
contains substantial drill cuttings and other solids.
Choke 130 is one such type and is further capable of
operating at variable pressures, flowrates and through
multiple duty cycles.

The drilling fluid 150 exits the choke 130 and flows
through an optional flow meter 126 to be directed through
an optional degasser 1 and solids separation
equipment 129. Optional degasser 1 and solids separation
equipment 129 are designed to remove excess gas and other
contaminates, including cuttings, from the drilling
fluid 150. After passing solids separation equipment 129,
the drilling fluid 150 is returned to reservoir 136.

Flow meter 126 may be a mass-balance type or other
high-resolution flow meter. A back pressure sensor 147
can be optionally provided in the drilling fluid
discharge conduit 124 upstream of the variable flow
restrictive device. A flow meter, similar to flow
meter 126, may be placed upstream of the back pressure
means 131 in addition to the back pressure sensor 147.

Back pressure control means including a pressure
monitoring system 146 are provided for monitoring data
relevant for the annulus pressure, and providing control
signals to at least the back pressure system 131 and

- 13 -

optionally also to the injection fluid injection system
and/or to the primary pump means.

The ability to provide adjustable back pressure
during the entire drilling and completing process is a
5   significant improvement over conventional drilling
systems, in particular in relation to UBD where the
drilling fluid pressure must be maintained as low as
possible in the operational window.

In general terms, the required back pressure to
10   obtain the desired down hole pressure is determined by
obtaining information on the existing down hole pressure
of the drilling fluid in the vicinity of the BHA 113,
referred to as the bottom hole pressure, comparing the
information with a desired down hole pressure and
15   utilizing the differential between these for determining
a set-point back pressure and controlling the back
pressure means in order to establish a back pressure
close to the set-point back pressure.

The pressure of the injection fluid in the injection
20   fluid supply passage 141 is advantageously utilized for
obtaining information relevant for determining the
current bottom hole pressure. As long as the injection
fluid is being injected into the drilling fluid return
stream, the pressure of the injection fluid at the
25   injection depth can be assumed to be equal to the
drilling fluid pressure at the injection point 144. Thus,
the pressure as determined by injection fluid pressure
sensor 156 can advantageously be utilized to generate a
pressure signal for use as a feedback signal for
30   controlling or regulating the back pressure system.

It is remarked that the change in hydrostatic
contribution to the down hole pressure that would result
from a possible variation in the injection fluid
injection rate, is in close approximation compensated by
35   the above described controlled re-adjusting of the back

- 14 -

pressure means. Thus by controlling the back pressure
means in accordance with the invention, the fluid
pressure in the bore hole is almost independent of the
rate of injection fluid injection.

5   One possible way to utilize the pressure signal
corresponding to the injection fluid pressure, is to
control the back pressure system so as to maintain the
injection fluid pressure on a certain suitable constant
value throughout the drilling or completion operation.

10   The accuracy is increased when the injection point 144 is
in close proximity to the bottom of the bore hole.

When the injection point 144 is not so close to the
bottom of the bore hole, the magnitude of the pressure
differential over the part of the drilling fluid return

15   passage stretching between the injection point 144 and
the bottom of the hole is preferably to be established.
For this, a hydraulic model can be utilized as will be
described below.

Figure 3 is a block diagram of a possible pressure

20   monitoring system 146. System inputs to this monitoring
system 146 include the injection fluid pressure 203 that
has been measured by the injection fluid pressure
sensor 156, and can include the down hole pressure 202
that has been measured by sensor package 119, transmitted

25   by MWD pulser package 122 (or other telemetry system) and
received by transducer equipment (not shown) on the
surface. Other system inputs include pump pressure 200,
input flow rate 204 from flow meter 152 or from mud pump
strokes compensated for efficiency, penetration rate and

30   string rotation rate, as well as weight on bit (WOB) and
torque on bit (TOB) that may be transmitted from the
BHA 113 up the annulus as a pressure pulse. Return flow
is optionally measured using flow meter 126, if provided.

Signals representative of the data inputs are

35   transmitted to a control unit (CCS) 230, which is in it

- 15 -

self comprised of a drill rig control unit 232, one or
more drilling operator's stations 234, a dynamic annular
pressure control (DAPC) processor 236 and a back pressure
programmable logic controller (PLC) 238, all of which are
5   connected by a common data network or industrial type
bus 240. In particular, the CCS 230 is arranged to
receive and collect data and make the data accessible via
the common data network or industrial type bus 240 to the
DAPC processor 236.

10   The DAPC processor 236 can suitably be a personal
computer based SCADA system running a hydraulic model and
connected to the PLC 238. The DAPC processor 236 serves
three functions, monitoring the state of the borehole
pressure during drilling operations, predicting borehole
15   response to continued drilling, and issuing commands to
the backpressure PLC to control the back pressure
means 131. In addition, commands may also be issued to
one or more of the primary pump means 138 and the
injection fluid injection system. The specific logic
20   associated with the DAPC processor 236 will be discussed
further below.

A schematic model of the functionality of the DAPC
pressure monitoring system 146 is set forth in Figure 4.
The DAPC processor 236 includes programming to carry out
25   control functions and Real Time Model Calibration
functions. The DAPC processor receives input data from
various sources and continuously calculates in real time
the correct backpressure set-point to achieve the desired
down hole pressure. The set-point is then transferred to
30   the programmable logic controller 238, which generates
the control signals for controlling the back pressure
means 131.

Still referring to Fig. 4, the pressure 263 in the
annulus at the injection fluid injection depth is
35   determined by means of a control module 259, thereby

- 16 -

utilizing some fixed well parameters 250 including depth
of the injection point 144, and some fixed injection
fluid data 255 such as specific mass of the injection
fluid, and some variable injection fluid injection
5   data 257 including at least pressure signal 203 generated
by injection fluid pressure sensor 156 and optionally
data such as the injection fluid injection rate.
Suitably, the injection fluid supply passage 141 is led
to the surface level on the rig, so that data generated
10   by the injection fluid pressure sensor 156 is readily
available as input signal for the back pressure control
system.

When N2, or another suitable gas, is used as the
injection fluid, the pressure in the annulus 115 at the
15   injection depth can be assumed to be equal to the
injection fluid pressure at surface compensated for the
weight of the injection fluid column. When a liquid is
used at any appreciable injection rate, a dynamic
pressure loss must be taken into account as well.

20   The pressure differential 262 over a lower part of
the annulus, the lower part stretching between the
injection point 144 and the bottom hole vicinity, is
added to the pressure 263 at the injection point 144.

The input parameters for determining this pressure
25   differential fall into three main groups. The first are
relatively fixed parameters 250, including parameters
such as well, drill string, hole and casing geometry,
drill bit nozzle diameters, and well trajectory. While it
is recognized that the actual well trajectory may vary
30   from the planned trajectory, the variance may be taken
into account with a correction to the planned trajectory.
Also within this group of parameters are temperature
profile of the fluid in the annulus and the fluid
composition. As with the geometrical parameters, these
35   are generally known and do not vary quickly over the

- 17 -

course of the drilling operations. In particular, with
the DAPC system, one objective is keeping the drilling
fluid 150 density and composition relatively constant,
using backpressure to provide the additional pressure for
5   control of the annulus pressure.

The second group of parameters 252 are highly
variable in nature and are sensed and logged in real
time. The rig data acquisition system provides this
information via common data network 240 to the DAPC
10   processor 236. This information includes injection fluid
pressure data 203 generated by injection fluid pressure
sensor 156, flow rate data provided by both down hole and
return flow meters 152 and 126 and/or by measurement of
pump strokes, respectively, the drill string rate of
15   penetration (ROP) or velocity, the drill string
rotational velocity, the bit depth, and the well depth,
all the latter being derived from direct rig sensor
measurements.

Furthermore, referring to Figures 1 and 4, down hole
20   pressure data 254 is provided by a pressure-sensing
tool 116, optionally via pressure data memory 205,
located in the bottom hole assembly 113. Data gathered
with this tool is transmitted to surface by the down hole
telemetry package 122. It is appreciated that most of
25   current telemetry systems have limited data transmission
capacity and/or velocity. The measured pressure data
could therefore be received at surface with some delay.
Other system input parameters are the desired set-point
for the down hole pressure 256 and the depth at which the
30   set-point should be maintained. This information is
usually provided by the operator.

A control module 258 calculates the pressure in the
annulus over the lower part well bore length stretching
between the injection point 144 and the bottom hole
35   utilizing various models. The pressure differential in

- 18 -

the well bore is a function not only of the static
pressure or weight of the relevant fluid column in the
well, but also includes pressures losses caused by
drilling operations, including fluid displacement by the
5   drill string, frictional pressure losses caused by fluid
motion in the annulus, and other factors. In order to
calculate the pressure within the well, the control
module 258 considers the relevant part of the well as a
finite number of elements, each assigned to a relevant
10   segment of well bore length. In each of the elements the
dynamic pressure and the fluid weight is calculated and
used to determine the pressure differential 262 for the
segment. The segments are summed and the pressure
differential for at least the lower end of the well
15   profile is determined.

It is known that the velocity of the fluid in the
well bore is proportional to the flow rate of the
fluid 150 being pumped down hole plus the fluid flow
produced from the formation 104 below the injection
20   point 144, the latter contribution being relevant for
under-balanced conditions. A measurement of the pumped
flow and an estimate of the fluid produced from the
formation 104 are used to calculate the total flow
through the bore hole and the corresponding dynamic
25   pressure loss. The calculation is made for a series of
segments of the well, taking into account the fluid
compressibility, estimated cutting loading and the
thermal expansion of the fluid for the specified segment,
which is itself related to the temperature profile for
30   that segment of the well. The fluid viscosity at the
temperature profile for the segment is also instrumental
in determining dynamic pressure losses for the segment.
The composition of the fluid is also considered in
determining compressibility and the thermal expansion
35   coefficient. The drill string movement, in particular its

rate of penetration (ROP), is related to the surge and swab pressures encountered during drilling operations as the drill string is moved into or out of the borehole. The drill string rotation is also used to determine dynamic pressure losses, as it creates a frictional force between the fluid in the annulus and the drill string. The bit depth, well depth, and well/string geometry are all used to help create the borehole segments to be modelled.

In order to calculate the weight of the drilling fluid contained in the well, the preferred embodiment considers not only the hydrostatic pressure exerted by fluid 150, but also the fluid compression, fluid thermal expansion and the cuttings loading of the fluid seen during operations. All of these factors go into a calculation of the "static pressure".

Dynamic pressure considers many of the same factors in determining static pressure. However, it further considers a number of other factors. Among them is the concept of laminar versus turbulent flow. The flow characteristics are a function of the estimated roughness, hole and string geometry and the flow velocity, density and viscosity of the fluid. The above includes borehole eccentricity and specific drill pipe geometry (box/pin upsets) that affect the flow velocity seen in the borehole annulus. The dynamic pressure calculation further includes cuttings accumulation down hole, string movement's (axial movement and rotation) effect on dynamic pressure of the fluid.

The pressure differential for the entire annulus is determined in accordance with the above, and compared to the set-point pressure 256 in the control module 264. The desired backpressure 266 is then determined and passed on to a programmable logic controller 238, which generates back pressure control signals.

- 20 -

The above discussion of how backpressure is generally calculated utilized several down hole parameters, including down hole pressure and estimates of fluid viscosity and fluid density. These parameters can be determined down hole, for instance using sensor package 119, and transmitted up the mud column using pressure pulses that travel to surface at approximately the speed of sound, for instance by means of telemetry system 122. This travelling speed and the limited bandwidth of such systems usually cause a delay between measuring the data down hole and receiving the data at surface. This delay can range from a few seconds up to several minutes. Consequently, down hole pressure measurements can often not be input to the DAPC model on a real time basis. Accordingly, it will be appreciated that there is likely to be a difference between the measured down hole pressure, when transmitted up to the surface, and the predicted down hole pressure for that depth at the time the data is received at surface.

For this reason, the down hole pressure data is preferably time stamped or depth stamped to allow the control system to synchronize the received pressure data with historical pressure predictions stored in memory. Based on the synchronised historical data, the DAPC system uses a regression method to compute adjustments to some input parameters to obtain the best correlation between predictions and measurements of down hole pressure. The corrections to input parameters may be made by varying any of the available variable input parameters. In the preferred embodiment, only the fluid density and the fluid viscosity are modified in order to correct the predicted down hole pressure. Further, in the present embodiment the actual down hole pressure measurement is used only to calibrate the calculated down

- 21 -

hole pressure. It is not utilized to directly adjust the
backpressure set-point.

Figure 5 shows an alternative embodiment of a
drilling system employing the invention. In addition to
the features already shown and described with reference
to the embodiment of Figures 1 to 4, the system of Fig. 5
includes a back pressure system 131 that is provided with
pressurizing means, here shown in the form of back
pressure pump 128, in parallel fluid communication with
the drilling fluid return passage 115 and the choke 130,
to pressurize the drilling fluid in the drilling fluid
discharge conduit 124 upstream of the flow restrictive
device 130. The low-pressure end of the back pressure
pump 128 is connected, via conduit 119, to a drilling
fluid supply which may be in communication with
reservoir 136. Stop valve 125' may be provided in
conduit 119 to isolate the back pressure pump 128 from
the drilling fluid supply.

Optionally, valve 123 may be provided to selectively
isolate the back pressure pump 128 from the drilling
fluid discharge system.

Back pressure pump 128 can be engaged to ensure that
sufficient flow passes the choke system 130 to be able to
maintain backpressure, even when there is insufficient
flow coming from the annulus 115 to maintain pressure on
choke 130. However, in UBD operations it may often
suffice to increase the weight of the fluid contained in
the upper part 149 of the well bore annulus by turning
down the injection fluid injection rate when the
circulation rate of drilling fluid 150 via the drill
string 112 is reduced or interrupted.

The back pressure control means in this embodiment
can generate the control signals for the back pressure
system, suitably adjusting not only the variable

- 22 -

choke 130 but also the back pressure pump 128 and/or
valve 123.

Figure 6 shows still another embodiment of the
drilling system, wherein in addition to the features of
Fig. 5, the drilling fluid reservoir comprises a trip
tank 2 in addition to the mud pit. A trip tank is
normally used on a rig to monitor fluid gains and losses
during tripping operations. It is remarked that the trip
tank may not be utilized that much when drilling using a
multiphase fluid system such as described hereinabove
involving injection of a gas into the drilling fluid
return stream, because the well may often remain alive or
the drilling fluid level in the well drops when the
injection gas pressure is bled off. However, in the
present embodiment the functionality of the trip tank is
maintained, for instance for occasions where a high-
density drilling fluid is pumped down instead in high-
pressure wells.

A manifold of valves is provided downstream of the
back pressure system 131, to enable selection of the
reservoir to which drilling mud returning from the well
bore is directed. In the embodiment of Fig. 5, the
manifold of valves includes two way valve 5, allowing
drilling fluid returning from the well or to be directed
to the mud pit 136 or the trip tank 2.

The back pressure pump 128 and valve 123 are
optionally added to this embodiment.

The manifold of valves may also include a two way
valve 125 provided for either feeding drilling fluid 150
from reservoir 136 via conduit 119A or from reservoir 2
via conduit 119B to a backpressure pump 128 optionally
provided in parallel fluid communication with the
drilling fluid return passage 115 and the choke 130.

In operation, valve 125 would select either
conduit 119A or conduit 119B, and the backpressure

pump 128 engaged to ensure sufficient flow passes the choke system to be able to maintain backpressure, even when there is no flow coming from the annulus 115.

In the embodiments shown and/or described above, the injection fluid supply passage is provided in the form of an outer annulus. The injection fluid supply passage may also be provided in a different form, for instance via a drill pipe gas injection system. This option is particularly advantageous when an outer annulus is no available for fluid injection. But more importantly, this option allows for the injection fluid injection point 144 to be located very close to the bottom of the hole so that the injection fluid pressure in the injection fluid supply passage gives an accurate parameter as a starting point for establishing an accurate value for the bottom hole pressure. Nevertheless, an electro-magnetic MWD sensor suite may be employed for pressure readout to be used in the same manner as described above to calibrate a hydraulics model.